

Compact Weather Sensors

Meteorology | Agrometeorology | Hydrology



General Description

The WS Series compact weather sensors are designed for **reliable and maintenance-free measurements** in hydrology, meteorology and weather-dependent applications where durability, precision and operations in different moderate climatic conditions and **wind speed up to 45 m/s** are required.

The compact devices allow for single or all-in-one measurements of up to 6 parameters such as

- Wind speed
- Wind direction
- Temperature
- Humidity
- Air-pressure
- Radiation

All sensors have been tested and approved against following environment conditions:

- High and low temperature ranges
- Humid weather (humidity and ingress protection)
- Windy and coastal environments (vibration and salt spray sustainability)

Applications

WeatherSens WS is especially suitable for hydro-meteorological and agrometeorological applications by one sensor design and construction, e.g. for

- Automatic weather stations - hydro
- Smart cities, urban areas and municipalities
- Road weather monitoring
- Power grid transmission stations
- Agrometeorological stations such as ETo or irrigation stations
- Photovoltaic farms
- Building automation
- Airfield and helicopter landing platforms

Features

- Wind speed measurement up to 45 m/s
- Low costs of installation and total costs of ownership
- Corrosion-resistant polycarbonate material, solid structure and rugged design
- Product portfolio to suit best to automatic weather monitoring
- Build-In data processing and algorithm
- Universal and selectable interfaces and protocols such as SDI-12 or RS 485 (MODBUS-RTU, ASCII, NMEA 0183)

- Easy integration into 3rd party systems
- Low power consumption for solar power packages
- No moving parts and maintenance-free with high IP grade 66
- Sustainability and high accuracy at entire wide temperature operating range from -40 to +70 °C (non-heated versions)
- Metric and imperial units
- Unheated versions: Operating measuring and deployment temperature range from -40 °C to +70° C

Accessories

- **M12 cables:** 10 m / 8-pol (sensor)
- **Poles:** with 2" or 50 mm outer diameter for 2 or 3.5 m measuring height
- **iRIS dataloggers and data modems:**
 - robust housing
 - IP over one or two channels of your choice: xG / GPRS, satellite, IoT
 - I/O: analog, digital, SDI-12, Modbus
 - iLink software
 - Telemetry or cloud app

[Please ask for details.](#)

Alternative: WeatherSens MP Series

MP Series compact weather sensors measure wind speed up to 75 m/s. With an aluminum alloy, teflon coating and an optional heater they are suitable for the harshest environments. [Please ask for details.](#)

Variants

WS200	WS500	WS650
		
Measures <ul style="list-style-type: none"> - wind speed - wind direction 	Measures <ul style="list-style-type: none"> - wind speed - wind direction - temperature - relative humidity - air pressure 	Measures <ul style="list-style-type: none"> - wind speed - wind direction - temperature - relative humidity - air pressure - solar radiation
H 152 x D 126 mm, 0.5 kg (H 5.98 x D 4.96 inch, 1.1 lbs) 20 mA @ 12 VDC *	H 208 x D 126 mm, 0.6 kg (H 8.19 x D 4.96 inch, 1.32 lbs) 23 mA @ 12 VDC *	H 233 x D 160 mm, 0.7 kg (H 9.17 x D 6.3 inch, 1.54 lbs) 27 mA @ 12 VDC *

Technical Specifications

IP Class	IP66
Interfaces	SDI-12 / RS 485 (selectable)
Protocols	SDI-12 V 1.3 or RS485 (MODBUS-RTU, ASCII, NMEA 0183)
Operating Voltage	10 to 30 VDC for all measuring parameters
Connector and Cable	Connector M12-8pol; Cable PUR 10 m (32.8 ft) (other lengths on request)
Operating Temperature	-40 °C to +70 °C (-40 to +158 °F)
Humidity	5 % to 100 % RH
Operating Measuring and Deployment Range	-40 °C to +70 °C (-40 to +158 °F) (without snow accumulation and/or ice accretion)

Parameters

	Wind Speed	Wind Direction	Temperature	Relative Humidity	Air Pressure	Solar Radiation
Principle	Ultrasonic	Ultrasonic	Diode voltage	Capacitive	Piezoresistor	Photoelectric
Range	0 to 45 m/s (0 to 100 mph)	0 to 359.9°	-40 to +80 °C (-40 to 176 °F)	0 to 100 % RH	10 to 1100 hPa	300 to 2100 nm; 0 to 2000 W/m ²
Accuracy	±0.3 m/s (±0.67 mph) or 3 %	±3°	±0.3 °C ** (±0.54 °F)	±3 % RH	±0.3 hPa	±5 %
Resolution	0.1 m/s (0.22 mph)	0.1°	0.1 °C (0.18 °F)	0.1 % RH	0.1 hPa	0.1 W/m ²

* Please note: With interface RS 485 the power consumption is 20 to 30 % less. Please ask for details.

** Accuracy in measuring range 0 to 40 °C (32 to 104 °F): ±0.2 °C (±32,4 °F)

Reseller

KISTERS Australia | sales@kisters.com.au | kisters.com.au
KISTERS Europe | hydromet.sales@kisters.eu | kisters.eu
KISTERS New Zealand | sales@kisters.co.nz | kisters.co.nz
KISTERS North America | kna@kisters.net | kisters.net

