

Designed For Reliability...

BU07

BUBBLER STANDARD ORIFICE

WATER LEVEL

General Description

The HyQuest Solutions standard orifice is designed to work with HS23A dry bubble unit. The BU07 permits the use of bubble rates at approx 27 bubble per minutes.

The standard orifice consist of a brass body that sits freely in a polyethylene cap with 2" GWI standard thread, it can be easily screwed to the end of the 2" GWI standard pipe,

The orifice body is made of copper to reduce aquatic growth and keeps the bubble flow constant at the rate required.

Features

- Robust construction
- Non corrosive material
- Easy Installation

Specifications

- Material
 - Cap polyethylene
 - Body copper
 - 2" GWI female thread
 - Plastic Ferrule
 - Stainless Steel Fitting
- Copper body to reduce aquatic growth
- Bubble rate to 24 bubbles/min
- Dimensions Dia 80mm x 55mm
- Weight 200g



N.B. Specifications are subject to change at any time without notice.

Contact Us

General Enquiries (Australia)

Phone: +61 2 9601 2022

Email: sales@hyquestolutions.com.au

Web: www.hyquestolutions.com.au

General Enquiries (New Zealand)

Phone: +64 (0) 7 857 0810

Email: sales@hyquestolutions.co.nz

Web: www.hyquestolutions.co.nz



HS HYQUEST
SOLUTIONS